

FARM-MAXX

Farm-Maxx FRG Series Root Grapple

54" - 60" - 66" - 72" ROOT GRAPPLES



Standard Features Include:

- AR400 Abrasion Resistant Steel
- Dual Cylinders on 60", 66", 72"
- Quick Attach Compatible
- 1/2" Male & Female Quick Connectors Included
- Tuff-Flex® Protective Hose Sleeve Standard

Optional:

- Flat Face Fittings

Model	FRG-54	FRG-60	FRG-66	FRG-72
Grapple Width	37.4" (949mm)	47.6" (1210mm)	51.7" (1314mm)	57.8" (1467mm)
Working Width	54" (1372mm)	60" (1528mm)	66" (1677mm)	72" (1829mm)
Overall Height	28.9" (7323mm)	28.9" (7323mm)	28.9" (7323mm)	28.9" (7323mm)
Grapple Opening	33" (813mm)	33" (813mm)	33" (813mm)	33" (813mm)
No. Teeth	6	8	8	9
Cylinders	1	2	2	2
HP Rating	60hp	60hp	60hp	60hp
Weight	315lb	359lbs	380lbs	401lbs



For more information contact:

Unifarm Machinery Corporation PO Box 38 (27894) 4608 Lely Road, Wilson, NC 27893
 Phone: 252-291-3997 Fax: 252-291-7354 Toll Free: 877-294-3997
 Email: sales@unifarm.biz Website: www.unifarmmachinery.com