

FARM-MAXX

FDM Drum Mowers

FDM-135 MINI, FDM-165, FDM-185, and FDM-210H



FDM Series Drum mowers feature robust durable construction for years of trouble free performance. Their simple design boasts one of the lowest power requirements in the industry. The result is low fuel consumption and longer tractor life. Switching from transport to mowing is simple and quick. Impact protection is provided by an automatic breakaway system. High quality swath and clean even cut will satisfy even the most demanding user.

Model	FDM-135 Mini	FDM-165	FDM-185	FDM-210H
Working Width	53"	66"	73"	83"
Drums	2	Double	Double	Double
Blades Per Drum	3	3	3	4
Quick Change Blades	Standard	Standard	Standard	Standard
Swath Width	24"	28"	32"	32"
Hitch Category	Cat 1	Cat I/II	Cat I/II	Cat I/II
Horsepower Minimum	22	35	40	65
Overrunning Clutch Internal	Standard	Standard	Standard	Standard
Transport Width	49"	60"	78"	78"
PTO	#5	#5	#5	#5
Drum Rotation Speed (RPM)	2,025	2,025	2,025	1,610
Blade Tip Speed (FPS)	233	295	338	295
Safety Breakaway	Standard	Standard	Standard	Standard
Hydraulic Fold	No	Optional	Optional	Standard
Working Speed (MPH)	9	9	9	9
Weight (LBS)	530	882	1,003	1,234



For more information contact:

Unifarm Machinery Corporation PO Box 38 (27894) 4608 Lely Road, Wilson, NC 27893

Phone: 252-291-3997 Fax: 252-291-7354 Toll Free: 877-294-3997

Email: sales@unifarm.biz Website: www.unifarmmachinery.com